

ST. LAWRENCE
WATERWAY PROJECT

PLATES
TO
ACCOMPANY APPENDICES
C. D. & E.

■

INDEX of PLATES

APPENDIX "C"

Plate No.	1 - Plan and Section of Typical Lock.
" "	2 - Diagram showing relation between Quantity of Concrete in Power Houses and Height-Draft Tube floor to coping.
" "	3 - Diagram showing relation between cost of Generators, Turbines, Exciters and Governors, and Maximum Operating Head.
" "	4 - Diagram showing relation between cost of switching per Horse Power and Maximum Operating Head.
" "	5 - Diagram showing relation between R.P.M. and cost of Generators and Exciters.
" "	6 - Diagram showing relation between Head and cost of Turbines and Governors.
" "	7 - Diagram showing relation between Head, c.f.s. per unit, and Throat Diameter.
" "	8 - Diagram showing relation between Head, Speed and Throat Diameter.
" "	9 - Types of Banks adopted for estimating purposes.
" "	10-16 - Thousand Island Section—Brockville to Clayton.

INTERNATIONAL RAPIDS SECTION

Plate No.	17-24 - Single Stage Scheme - 242.
" "	25 - Relation between surges on Lake Ontario and Barometric Pressure.
" "	26-33 - Two Stage Development - 224.
" "	34-38 - Two Stage Development - 217 - Chrysler Island.
" "	39-43 - Single Stage Development - 238.
" "	44-45 - Diagrams showing results of Backwater calculation.

LAKE ST. FRANCIS SECTION

Plate No.	46-48 - Project Recommended.
-----------	------------------------------

SOULANGES SECTION

Plate No.	49-50 - Project Recommended - 1st Stage of Ile aux Vaches Project.
" "	51 - Subsequent Stages of Ile aux Vaches Project
" "	52-53 - All River Development - Centre Pool Elev. 115.
" "	54-55 - All River Development - Centre Pool Elev. 125.
" "	56-57 - Navigation and Power Combined. Hungry Bay - Melocheville Route.
" "	58-59 - Alternative Navigation Project Hungry Bay - Melocheville Route.
" "	60-61 - Alternative Navigation Project. Lateral Canal on North side.

LACHINE SECTION

Plate No.	62-64 - Project Recommended.
" "	65-66 - Power Development Subsequent to Project Recommended.

APPENDIX "D"

Plate No.	1 - Derivation of Discharge Stage relation for Lock No. 25.
" "	2 - Relation between Gauge reading at Lock 25 and discharge of St. Lawrence River.
" "	3 - Relation between Gauge reading at Grenville, Que., and discharge of the Ottawa River.
" "	4 - Relation between Gauge reading at Upper St. Annes Lock and Discharge of Ottawa River into Des Prairies and Mille Iles Rivers.
" "	5 - Relation between Gauge reading at Upper St. Annes Lock and discharge of Ottawa River into Lake St. Louis.
" "	6 - Derivation of Discharge Stage for Lock No. 5, Lachine. Period 1860 - 1877.
" "	7 - Derivation of Discharge Stage for Lock No. 5, Lachine. Period 1904 to date.
" "	8 - Relation between Gauge reading at Lock No. 5, Lachine and Discharge of St. Lawrence River.
" "	9 - Relation between Gauge Reading at Pointe Claire, Que., and Discharge of St. Lawrence River.
" "	10 - Derivation of Discharge Stage for Lock No. 1, Lachine.
" "	11 - Typical Discharge Stage relation for Lock No. 1, Lachine.
" "	12 - Derivation of Discharge Stage for Varennes, Que.
" "	13 - Derivation of Discharge Stage for Sorel, Que.

APPENDIX "E"

Plate No.	1 - Air and Water Temperatures at various points. Lake Ontario to Montreal, 1921, 1922 and 1923.
" "	2 - Air and Water Temperatures at various points. Lake Ontario to Montreal, 1924, 1925 and 1926.
" "	3 - Effect of snowfalls and cold weather on height of ice jams in St. Lawrence River, 1913, 1916 and 1920.
" "	4 - Effect of snowfalls and cold weather on height of ice jams in St. Lawrence River, 1918, 1922 and 1923.
" "	5 - Effect of snowfalls and cold weather on height of ice jams in St. Lawrence River, 1923 and 1925.
" "	6 - Effect of snowfalls and cold weather on height of ice jams in St. Lawrence River, 1924, 1925 and 1926.
" "	7 - Relation between slope through ice packs and curvature of river.
" "	8 - Slush sections, St. Lawrence River,—Winter of 1923-24.
" "	9 - Slush sections, St. Lawrence River - Winter of 1923-24.

Joint Board of Engineers - Report.

TC 427

5356

1926a

Portfolio

McKenna

PRESENTED TO THE LIBRARY
BY THE GOVERNMENT OF
THE DOMINION OF CANADA

SFI

JGG




v.2




McGILL
UNIVERSITY
LIBRARY

ACC. NO. 229829 DATE 1928


473346



SECTION B-B



SECTION A-A




SECTION C-C


ST. LAWRENCE WATERWAY


PLAN AND SECTIONS
SHOWING
PROPOSED CASCADES PT. LOCK


Scale of Feet
50 40 30 20 10 0 50 100

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926.










Note :- These are Canadian Prices - For U.S. Prices take 78%.

Cost of Generators per Kv.a and Exciters (38¢ per lb) in dollars.

ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 RELATION BETWEEN R.P.M.
 AND
 COST OF GENERATORS AND EXCITERS

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED NOV. 16TH 1926.




Cost F.O.B. Shop per $\frac{\text{H.P.}}{1/10 \text{ Head}}$ of Turbines and Governors in dollars

Add 12½% for erection and freight.

ST. LAWRENCE WATERWAY

DIAGRAM SHOWING
RELATION BETWEEN HEAD
AND COST OF
TURBINES AND GOVERNORS

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926.




Ratio of $\frac{\text{c.to c. spacing}}{\text{Throat Diam.}} = \begin{cases} 3.0 \text{ Elbow Draft Tube} \\ 3.6 \text{ Moody} \end{cases}$

ST. LAWRENCE WATERWAY

DIAGRAM SHOWING
RELATION BETWEEN HEAD
C.F.S PER UNIT
AND THROAT DIAMETER


TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926.





ST. LAWRENCE WATERWAY


DIAGRAM SHOWING
RELATION BETWEEN HEAD
SPEED
AND THROAT DIAMETER


TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH. 1926.



























Gage N ^o	WATER ELEVATIONS		
	For Discharge of		
	216,000	247,000	250,000
1	230.2	231.9	233.6
2	227.0	228.99	230.9
3	226.4	228.0	230.0
4	226.2	227.6	230.0
5	224.6		
6	223.9	225.7	227.6
7	223.7	225.5	227.3
8	221.5	224.3	226.1
9		222.7	224.2
10		219.3	
11	216.0	215.5	220.3
12	213.2	215.0	216.0

Rock elevations from Deep Waterway Board 1900 borings shown thus

Rock elevations from Hyco-Electric borings	○△□
Rock elevations from previous borings	△□○
Rock elevations from well drill 1925	△□○
Rock elevations from wash borings 1925	△□○
Rock elevations from core borings 1925	△□○
Bottom of borings not reaching rock ---	○△□



WATER ELEVATIONS			
Gage No	For Discharge of		
	216 000	247 000	280 000
1		206.4	207.5
2		206.4	207.6
3	204.8		
4	203.1		
5		202.5	203.3
6	204.3	206.4	207.4
7	200.7	202.1	
8		203.2	206.2
9	202.5	204.4	
10	200.6	202.3	203.1
11	200.65	201.75	
12	202.5	204.4	
13		204.1	


ST. LAWRENCE WATERWAY
INTERNATIONAL POWER SECTION
IMPROVEMENT PRESENTED BY
AMERICAN SECTION

SHEET 5

SCALE OF FEET

*To accompany Report of Joint Board of Engineers
dated November 16, 1926.*

*All elevations refer to Mean Sea Level,
New York Harbor, 1903 adjustment.*





ST. LAWRENCE WATERWAY
INTERNATIONAL POWER SECTION
IMPROVEMENT PRESENTED BY
AMERICAN SECTION

SHEET 7

SCALE OF FEET
1000 0 1000 2000 3000


To accompany Report of Joint Board of Engineers
dated November 16, 1926.


All elevations refer to Mean Sea Level,
New York Harbor, 1903 adjustment.

WATER ELEVATIONS

Gage No.	For Discharge of		
	216,000	247,000	280,000
1	156.7	159.05	160.0
2	154.9	156.15	157.2
3	156.5		
4	153.4	155.2	156.1
5	152.6	153.7	154.6
6	152.45	153.56	154.26
7	152.25	153.2	154.1
8	152.1	153.1	154.0

Rock elevations from borings ---- R 160
Bottom of borings not reaching rock --- @ 150
International Boundary Monuments ----







ST. LAWRENCE WATERWAY
DIAGRAM SHOWING
RELATION BETWEEN SURGES ON
LAKE ONTARIO
AND
BAROMETRIC PRESSURE

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926

Note: Water Levels obtained from Records supplied by Dept. of Marine & Fisheries.








ST. LAWRENCE WATERWAY
INTERNATIONAL RAPIDS SECTION
PLAN SHOWING
PROJECT PRESENTED BY CANADIAN SECTION
TWO STAGE DEVELOPMENT - 224
MILE 70 TO MILE 78
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926


Rock elevations from previous borings • R168
Bottom of borings, not reaching rock • R190
Rock elevations from core borings of 1925 • R180
Rock elevations from mesh borings of 1925 • R180
Rock elevations found in excavation of canal • R180
Borings by Ohio Waterway Board, 1902, showing rock at right
elevation under Sparrowhawk Point omitted as disproved
by subsequent borings.
Rock elevations from well drill • R180

Gage No.	WATER ELEVATIONS For Discharge of		
	216,000	247,000	280,000
1	243.21	244.95	
2	242.07	243.42	
3	240.61	241.86	
4	238.54	239.58	
5	233.38	235.35	
6	231.4	233.1	235.1
7	242.96	244.37	
8	242.18	243.57	
9	242.68	244.01	
10	238.28	239.85	
11	236.67	238.45	
12	238.26	239.32	
13	235.13	236.98	
14	235.54	235.47	
15	233.8	234.9	237.1
16	231.5	233.2	235.2
17	230.4	231.9	233.9













SCALE OF FEET


To accompany report of Joint Board of Engineers
dated Nov. 16th 1926

WATER ELEVATIONS			
Gage No	For Discharge of		
	216000	247000	289000
1	156.7	158.05	160.00
2	154.9	156.15	157.7
3	156.5		
4	153.4	155.2	156.1
5	152.8	153.7	154.6
6	152.45	153.56	154.2
7	152.25	153.2	154.1
8	152.1	153.1	154.0

Rock elevations from borings ---- • R 168
Bottom of borings not reaching rock -- • 160
International Boundary Monuments ---- •








ST. LAWRENCE WATERWAY
INTERNATIONAL RAPIDS SECTION
PLAN SHOWING
ALTERNATIVE PROJECT PRESENTED
TWO STAGE DEVELOPMENT - 217
MILE 70 TO MILE 78
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926


Rock elevations from previous borings R-168
Bottom of borings, not reaching rock R-180
Rock elevations from core borings of 1925 R-180
Rock elevations from west borings of 1925 R-180
Rock elevations found in excavation of canal R-180
Borings by Dept. of Marine Board, 1900, showing rock at high
elevation under Sparrowhawk Point omitted as discovered
by subsequent borings.
Rock elevations from well drill R-182


Gage No.	WATER ELEVATIONS For Discharge of		
	216000	247000	280000
1	243.21	244.55	
2	242.07	243.42	
3	240.61	241.86	
4	238.54	239.58	
5	235.38	235.35	
6	231.4	235.1	235.1
7	242.96	244.37	
8	242.18	243.57	
9	242.68	244.01	
10	238.28	239.85	
11	236.67	238.45	
12	238.26	239.32	
13	235.13	236.98	
14	233.54	235.47	
15	233.8	234.9	237.1
16	231.5	233.2	235.2
17	230.4	231.9	233.9





Gage No	WATER ELEVATIONS For Discharge of		
	215,000	247,000	250,000
1	230.2	231.9	233.6
2	227.0	225.99	230.8
3	226.4	225.0	230.0
4	226.2	227.6	230.0
5	224.6		
6	223.9	225.7	227.6
7	223.7	225.5	227.3
8	221.5	224.3	226.1
9		222.7	224.2
10		219.3	
11	216.6	216.5	220.3
12	213.2	215.0	216.8

Rock elevations from Deep Waterway Board 1900 borings shown thus: 19.0
Rock elevations from Hydro-Electric borings: 19.0
Rock elevations from previous borings: 19.0
Rock elevations from well drill 1925: 19.0
Rock elevations from wash borings 1925: 19.0
Rock elevations from core borings 1925: 19.0
Bottom of borings not reaching rock: 19.0










ST. LAWRENCE WATERWAY
INTERNATIONAL RAPIDS SECTION
PLAN SHOWING
ALTERNATIVE PROJECT CONSIDERED
SINGLE STAGE DEVELOPMENT - 238
MILE 70 TO MILE 78

SCALE OF FEET
1000 0 2000 3000

To accompany report of Joint Board of Engineers
dated Nov. 16th 1926

Rock elevations from previous borings ----- R-160
Bottom of borings, not reaching rock ----- R-180
Rock elevations from core borings of 1925 ----- R-160
Rock elevations from wash borings of 1925 ----- R-180
Rock elevations found in excavation of canal ----- R-180
Borings by Dept. of Waterways Board, 1906, showing rock at high
elevation under Sparrowhawk Point omitted as disproved
by subsequent borings.
Rock elevations from well drill ----- R-180

Gage No.	WATER ELEVATIONS For Discharge of		
	216,000	241,000	280,000
1	243.21	244.55	
2	247.07	243.42	
3	240.61	241.86	
4	238.54	239.58	
5	233.38	235.35	
6	231.4	233.1	235.1
7	242.96	244.37	
8	242.18	243.57	
9	242.68	244.01	
10	238.28	239.85	
11	236.67	238.45	
12	238.26	239.32	
13	235.13	236.98	
14	233.54	235.47	
15	233.9	234.9	237.1
16	231.5	233.2	235.2
17	230.4	231.9	233.9





**ST. LAWRENCE WATERWAY
INTERNATIONAL RAPIDS SECTION**
PLAN SHOWING
ALTERNATIVE PROJECT CONSIDERED
SINGLE STAGE DEVELOPMENT - 238
MILE 78 TO MILE 85


SCALE OF FEET
1000 0 1000 2000 3000
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926


Gage No.	WATER ELEVATIONS For Discharge of		
	219,000	247,000	280,000
1	230.2	231.9	233.8
2	227.0	228.59	230.9
3	226.4	228.0	230.0
4	226.2	227.6	230.0
5	224.6		
6	223.9	225.7	227.6
7	223.7	225.5	227.3
8	221.5	224.3	226.1
9		222.7	224.2
10		219.3	
11	218.6	216.5	220.3
12	213.2	215.0	216.8

Rock elevations from Deep Waterway Board 1900 borings shown thus
Rock elevations from Hydro-Electric borings
Rock elevations from previous borings
Rock elevations from well drill 1925
Rock elevations from wash borings 1925
Rock elevations from core borings 1925
Bottom of borings not reaching rock











- | | | |
|---|--------------------------------|----------------------------------------------------------------------|
| ① | W.L. Barnhart Isd. Po. Ho. 238 | - All gates in diversion open-Flow in South Galap 75,000 c.f.s. |
| ② | " " " " | - All gates in diversion closed- |
| ③ | " " " " | - All gates in both dams open. |
| ④ | " " " " | - One-half gates in diversion open-Flow in South Galap 75,000 c.f.s. |
| ⑤ | " " " " | 236 - All gates in both dams open. |
| ⑥ | " " " " | 238 - All gates in diversion closed. All gates in South Galap open. |
| ⑦ | " " " " | - All gates in both dams closed. |

All gates in Diversion closed All gates in South Galop open.			All gates in both dams open.		
W.L. Lake Ont.	Q-South Galop	H-Sub sluices	W.L. Lake Ont.	Q-South Galop	H-Sub sluices
244.44	100,000	1.8	243.65	75,000	1.0
245.60	110,000	2.15	244.30	80,000	1.15
246.90	120,000	2.55	244.95	85,000	1.3
248.05	130,000	3.0	245.65	90,000	1.45
249.00	138,000	3.4	246.40	95,000	1.6
			247.20	100,000	1.8
			247.80	108,000	2.1


Note:- Shaded portion shows Range between Maximum and Minimum Discharges under regulation - April to December.



Note :- Computations made by Canadian Section.




Note :- All gates in Control Dams open. Shaded portion shows Range between Maximum and Minimum Discharges under regulation for 2nd half Dec. Jan & Feb.



ST LAWRENCE WATERWAY "238" SCHEME

DIAGRAM SHOWING RESULTS OF
BACKWATER CALCULATIONS
Barnhart Isd. Powerhouse to Lake Ontario


TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926.




Note:- Computations made by Canadian Section.


**ST. LAWRENCE WATERWAY
"238" SCHEME**
Diagram showing the relation between
HEAD on SUBMERGED SLUICES at GALOP
and
FLOW under REGULATION
TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926.

APPENDIX 'C' PLATE 46








ST. LAWRENCE WATERWAY
LAKE ST. FRANCIS SECTION
PLAN SHOWING
PROJECT RECOMMENDED
MILE 124 TO MILE 133
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926



ST. LAWRENCE WATERWAY
LAKE ST. FRANCIS SECTION
PLAN SHOWING
PROJECT RECOMMENDED
MILE 133 TO MILE 141
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926








ST. LAWRENCE WATERWAY
SOULAGES SECTION

PLAN SHOWING
 PROJECT RECOMMENDED
 WITH SUBSEQUENT
 DEVELOPMENT FOR POWER
 MILE 150 TO MILE 158


SCALE OF FEET


To accompany report of Joint Board of Engineers
 dated Nov. 16th, 1926





ST. LAWRENCE WATERWAY
SOULANGES SECTION
PLAN SHOWING
ALL RIVER DEVELOPMENT
CENTRE POOL ELEV. 115
MILE 141 TO MILE 150

SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926










SCALE OF FEET


To accompany report of Joint Board of Engineers
dated Nov. 16th 1926




ST. LAWRENCE WATERWAY
SOULANGES SECTION
PLAN SHOWING
ALTERNATIVE NAVIGATION PROJECT
HUNGRY BAY - MELOCHEVILLE ROUTE
MILE 141 TO MILE 150


SCALE OF FEET

To accompany report of Joint Board of Engineers
dated Nov. 16th 1936




ST. LAWRENCE WATERWAY
SOULANGES SECTION
PLAN SHOWING
ALTERNATIVE NAVIGATION PROJECT
HUNGRY BAY - MELOCHEVILLE ROUTE
MILE 150 TO MILE 159
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th, 1925







ST. LAWRENCE WATERWAY
SOULANGES SECTION
PLAN SHOWING
ALTERNATIVE NAVIGATION PROJECT
LATERAL CANAL ON NORTH SIDE
MILE 150 TO MILE 159
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926



ST. LAWRENCE WATERWAY
LACHINE SECTION
PLAN SHOWING
PROJECT RECOMMENDED
MILE 158 TO MILE 167
SCALE OF FEET
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926




ST. LAWRENCE WATERWAY
LACHINE SECTION
PLAN SHOWING
PROJECT RECOMMENDED
MILE 167 TO MILE 176
SCALE OF FEET
0 1000 2000
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926



ST. LAWRENCE WATERWAY
LACHINE SECTION
PLAN SHOWING
PROJECT RECOMMENDED
WITH SUBSEQUENT
DEVELOPMENT FOR POWER
MILE 167 TO MILE 176


SCALE OF FEET


To accompany report of Joint Board of Engineers
dated Nov. 16th 1926




ST. LAWRENCE WATERWAY
LACHINE SECTION
PLAN SHOWING
PROJECT RECOMMENDED
WITH SUBSEQUENT
DEVELOPMENT FOR POWER
MILE 176 TO MILE 183

SCALE OF FEET
0 100 200
To accompany report of Joint Board of Engineers
dated Nov. 16th 1926










ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 RELATION BETWEEN GAUGE READING
 GRENVILLE QUE.
 AND
 DISCHARGE OF OTTAWA RIVER
 INTO DES PRAIRIE AND MILLE ILES RIVERS
 TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED NOV. 16TH 1926





















Water Surface Elevations at Lock No 1 Lachine.











ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 AIR AND WATER TEMPERATURES
 AT VARIOUS POINTS
 LAKE ONTARIO TO MONTREAL

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED NOV. 16TH 1926




ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 AIR AND WATER TEMPERATURES
 AT VARIOUS POINTS
 LAKE ONTARIO TO MONTREAL

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED NOV. 16TH 1926




ST. LAWRENCE WATERWAY
DIAGRAM SHOWING
EFFECT OF SNOWFALLS AND
COLD WEATHER ON HEIGHT OF
ICE JAMS IN
ST. LAWRENCE RIVER
TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED NOV. 16TH 1926



WATER LEVELS AT
Lock 23, Weavers Pt., Upper Farrans Pt. and
Woodlands Dock, only.


ST. LAWRENCE WATERWAY
DIAGRAM SHOWING
EFFECT OF SNOWFALLS AND
COLD WEATHER ON HEIGHT OF
ICE JAMS IN
ST. LAWRENCE RIVER

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
DATED, NOV. 16TH 1926.




ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 EFFECT OF SNOWFALLS AND
 COLD WEATHER ON HEIGHT OF
 ICE JAMS IN
 ST. LAWRENCE RIVER



TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED NOV. 16TH 1926.




ST. LAWRENCE WATERWAY
 DIAGRAM SHOWING
 EFFECT OF SNOWFALLS AND
 COLD WEATHER ON HEIGHT OF
 ICE JAMS IN
 ST. LAWRENCE RIVER

TO ACCOMPANY REPORT OF JOINT BOARD OF ENGINEERS
 DATED, NOV. 16TH 1926







SLUSH SECTIONS
ST. LAWRENCE RIVER
WINTER 1923 -24

Scales

1 in. Horizontal	=	400 Feet.
1 in. Vertical	=	10 Feet.

